





New 48" Length Thin Wall Colors!



H E A T S H R I N K T U B I N G

Thin Wall Cross-Linked Polyolefin

- Available in 25/50 and 100' spools, 48" and 6" lengths and prepackaged assortments

Dual Wall Cross-Linked Polyolefin With Adhesive

- Available in 48" and 6" lengths

Medium Wall Cross-Linked Polyolefin

- Available in 48" lengths

Thick Wall Cross-Linked Polyolefin

- Available in 48" lengths



FEATURES:

- Shrink ratio
 - Thin wall: 2:1
 - Dual wall: 3:1
 - Medium wall: 3:1
 - Thick wall: 3:1
 - Continuous operating temperature
 - Thin wall: -55°C to 135°C
 - Dual wall: -55°C to 85°C
 - Medium wall: -40°C to 120°C
 - Thick wall: -40°C to 120°C
 - Shrink temperature
 - Thin wall: >90°C
 - Dual wall: >110°C
 - Medium wall: >110°C
 - Thick wall: >110°C
 - Resistant to common fluids and solvents
 - All product is UL and CSA listed
- Meets DEF. STAN 59.97*
 - Meets UL 224, 125°C and CSA C22.2 No. 198.1*
 - Meets:
 - Thin wall: MIL-DTL-23053/5 Class 2 & 3
 - Dual wall: MIL-DTL-23053/4 Class 3
 - Flame retardant (Does not include transparent)
 - Thin wall
 - Dual wall: Outer wall only
 - Seals and protects cable splices and terminations**
 - The medium and thick wall series are ideally suited for underground and direct burial
 - Available in many colors
 - *Medium & thick wall available In black only

*Thin Wall **Dual Wall

www.nteinc.com

HEAT SHRINK TUBING

ASSORTED THIN WALL PACKAGES:

| Model | Color | Pieces | Bag/Box | Length (Inches) | Diameter (Inches) |
|------------|---|--------|---------|-----------------|---|
| HS-ASST-1 | Black | 24 | Bag | 6 | 3/32, 1/8, 3/16, 1/4, 3/8, 1/2 (4 pieces of each diameter) |
| HS-ASST-2 | Black | 158 | Box | 2 1/2 | 1/16 (60 pieces), 1/8 (40 pieces), 3/16 (20 pieces), 1/4 (18 pieces), 3/8 (10 pieces), 1/2 (10 pieces) |
| HS-ASST-3 | Red | 158 | Box | 2 1/2 | 1/16 (60 pieces), 1/8 (40 pieces), 3/16 (20 pieces), 1/4 (18 pieces), 3/8 (10 pieces), 1/2 (10 pieces) |
| HS-ASST-4 | Black | 28 | Bag | 4 | 1/16, 3/32, 1/8, 3/16, 1/4, 3/8, 1/2 (4 pieces of each diameter) |
| HS-ASST-5 | (2) Black, (2) Red, (2) Clear, (1) Green, (1) Blue, (1) Yellow, (1) White | 10 | Bag | 6 | 1/8 |
| HS-ASST-6 | (2) Black, (2) Red, (2) Clear, (1) Green, (1) Blue, (1) Yellow, (1) White | 10 | Bag | 6 | 3/16 |
| HS-ASST-7 | (2) Black, (2) Red, (2) Clear, (1) Green, (1) Blue, (1) Yellow, (1) White | 10 | Bag | 6 | 1/4 |
| HS-ASST-8 | (2) Black, (2) Red, (2) Clear, (1) Green, (1) Blue, (1) Yellow, (1) White | 10 | Bag | 6 | 3/8 |
| HS-ASST-9 | Black, Red, Clear, Green, Blue, Yellow, White | 160 | Box | 4 | 1/16 (60 pieces), 3/32 (35 pieces), 1/8 (25 pieces), 3/16 (20 pieces), 1/4 (10 pieces), 3/8 (10 pieces) |
| HS-ASST-10 | (2) Black, (2) Red, (2) Clear, (1) Green, (1) Blue, (1) Yellow, (1) White | 10 | Bag | 6 | 1/16 |
| HS-ASST-11 | (2) Black, (2) Red, (2) Clear, (1) Green, (1) Blue, (1) Yellow, (1) White | 10 | Bag | 6 | 3/32 |
| HS-ASST-12 | (2) Black, (2) Red, (2) Clear, (1) Green, (1) Blue, (1) Yellow, (1) White | 10 | Bag | 6 | 1/2 |



NTE Electronics Inc.,
44 Farrand Street
Bloomfield, NJ 07003
Phone: 973-748-5089 Fax: 973-748-6224
www.ntelinc.com

